

Performus I Dispenser

For operator-controlled dispensing applications that do not require a timed shot



Used for applications that do not require a timed shot.

Part #	Description
7012330	Performus I, 0-100 psi (0-7 bar) Vacuum

Nordson EFD's Performus™ dispensers increase throughput, improve yields, and reduce production costs through controlled application of adhesives, lubricants and other assembly fluids.

Features

- Handles all fluids
- Vacuum control keeps thin fluids from dripping
- Electric foot pedal

Benefits

- Fast, controlled application
- Makes dots, beads and fills
- Clean, drip-free cutoff
- Less operator fatigue
- Compact design



more info



Specifications

Item	Specification
Cabinet size	183 _w x 51 _H x 86 _D mm (7.22 _w x 2 _H x 3.38 _D ")
Weight	1 Kg (2.2 lb)
Power adapter	AC input: 100-240 VAC, ~50/60Hz DC output: 24 VDC @ 1.04A
Initiate circuits	Foot pedal, finger switch
Cycle rate	Exceeds 600 cycles per minute
Power requirements	24 VDC – 1.04 Amp maximum
DC input power required	8W-20W
Internal voltage	24 VDC
Footswitch	Voltage: 24 VDC0 Current: 20mA
Air Input requirements	100 psi (7 bar) maximum
Air Output	1-100 psi (1-7 bar) dependent on user setting
Ambient operating conditions	Temperature: 5°C to 45°C (41°F-113°F) Humidity: 85% RH at 30°C (86°F) non-condensing Height above sea level: 2000 meters (6562 ft) maximum
Approvals	CE, CSA, RoHS, WEEE & China RoHS Compliant Meets or exceeds CE and CSA requirements

Request a Process Evaluation


Contact Nordson EFD to configure a precision dispense system that meets your specific needs, with:

- A complimentary process evaluation by experienced fluid dispensing experts.
- Samples processed for customer evaluation and approval prior to purchase.

Don't Forget to Order Your Components

EFD Optimum® components are designed to work with your dispenser as part of a complete, integrated system that produces the most accurate, repeatable deposits possible.

- Adapter assembly
- Syringe barrels
- SmoothFlow™ pistons
- Dispensing tips
- Tip caps and end caps



For Nordson EFD sales and service in over 40 countries, contact Nordson EFD or go to www.nordsonefd.com.

Global

East Providence, RI USA
800-556-3484; +1-401-431-7000
info@nordsonefd.com

Europe

Dunstable, Bedfordshire, UK
0800 585733; +44 (0) 1582 666334
europe@nordsonefd.com

Asia

China: +86 (21) 3866 9006; china@nordsonefd.com
India: +91 80 4021 3600; india@nordsonefd.com
Japan: +81 03 5762 2760; japan@nordsonefd.com
Korea: +82-31-736-8321; korea@nordsonefd.com
SEAsia: +65 6796 9522; sin-mal@nordsonefd.com

©2017 Nordson Corporation v121417