

Precision Dispensing Tips

Luer Lok Adapters and Luer Needles

Luer Lok Adapters (locking hubs) are used for attaching Dispensing Tips to mixers. When ordering, simply add the suffix “LL” to the mixer. If you want to use a metal jacket with the 3/16”ID and 1/4”ID bell mixers, order the mixer and the Luer Lok fitting (7700943) as two separate items unassembled (needs to order SH version of mixer).

Dispensing Tips

Nordson EFD produces the highest quality dispensing tips in the industry. All tips are produced in silicone-free facilities, and subjected to stringent quality control inspections throughout the entire manufacturing process.

Features and Benefits

- Free of flash, burrs and contaminants
- Package labels include lot numbers for process control and traceability
- Consistent from style to style and lot to lot
- 360° SafetyLok™ thread ensures safe, positive attachment to syringe barrel
- Engineered hub flats for easy twist on, twist off

Precision Stainless Steel Passivated stainless steel tips handle a wide range of fluids and applications.

Tapered Smooth flow for application of medium- to high-viscosity fluids – especially thick or particle-filled materials like epoxies, RTVs and braze pastes.

Flexible Polypropylene shafts reach into hard-to-access areas and will not scratch delicate surfaces. Easily cut to size or angled as needed.

Angled Stainless steel tips are available with 45° and 90° bends.












Brush For spreading glues and greases. Available with soft or stiff bristles.

Specialty For specific applications: chamfered, ESD-safe, PTFE-coated and PTFE-lined, microdot tips and oval tips.




Precision Dispensing Tips

Precision Stainless Steel Tips

Gauge	6.35 mm (0.25")	12.7 mm (0.50")	25.4 mm (1.0")	38.1 mm (1.5")	45° Bend/12.7 mm (0.5")	90° Bend/12.7 mm (0.5")	45° Bend/38.1 mm (1.5")	Color
14	7018029	7018043	7018032	7018035	7018044	7018045	7016906	Olive 
15	7018056	7018068	7018059	7018062	7018069	7018070	n/a	Amber 
18	7018107	7018122	7018110	7018113	7018123	7018124	7016908	Green 
20	7018163	7018178	7018166	7018169	7018179	7018180	n/a	Pink 
21	7005005	7018233	7018222	7018225	7018234	7018235	7016910	Purple 
22	7018260	7018272	7018263	7018266	7018273	7018274	n/a	Blue 
23	7018302	7018314	7018305	7018308	7018315	7018316	n/a	Orange 
25	7018333	7018345	7018336	7018339	7018346	7018347	n/a	Red 
27	7018395	7005008	n/a	n/a	7018404	7018405	n/a	Clear 
30	7018424	7018433	n/a	n/a	7018434	7018435	n/a	Lavender 
32	7018462	n/a	n/a	n/a	n/a	n/a	n/a	Yellow 





Burr-free, polished, passivated stainless steel dispensing tips with polypropylene SafetyLok hubs for a secure fit to barrel reservoirs. Packaged 50 tips per box.
 • 6.35 mm (0.25") tips: Fast point-to-point dispensing. • 12.7 mm (0.50") tips: Standard all-around precision dispensing tips. • 45° and 90° bent tips: Easy access into hard-to-reach areas.

Smoothflow Tapered Tips

Gauge	Standard	Opaque Rigid	Color
14	7018052	7018049	Olive 
16	7018100	7018097	Grey 
18	7018158	7018147	Green 
20	7005009	7005006	Pink 
22	7018298	7005007	Blue 
25	7018391	7018370	Red 
27	7018417	n/a	Clear 

Use with gel cyanoacrylates, UV-cure adhesives, sealants, and particle-filled materials or any medium- to high-viscosity fluid. Molded of polyethylene with UV-light block additive. Packaged 50 tips per box.

Flexible Tips

Gauge	12.7 mm (0.50")	38.1 mm (1.5")	Color
15	7018085	7018080	Amber 
18	7018143	7018138	Green 
20	7018205	7018201	Pink 
25	7018366	7018362	Red 

Flexible polypropylene tubing for application into difficult-to-access areas. Easily drags along edges and around corners and prevents scratching. Tubing can be cut to length. Packaged 50 tips per box.



Brush Tips

Style	Standard	High Flow
soft bristle	7018490	7018491
stiff bristle	7018494	7018495

Spread glues and greases. Nylon bristles, 50.8 mm (2") length. Sold individually.





PTFE-Coated Tips

Gauge	ID	OD	12.7 mm (0.50")	Color
21	0.020	0.033	7018243	Purple 
23	0.013	0.026	7018326	Orange 

Controls wicking to stop drips in optical media applications. Packaged 20 tips per box.

PTFE-Lined Tips

ID	12.7 mm (0.50")	25.4 mm (1.0")	Color
0.020"	7018256	7005003	Grey 
0.006"	7018388	7005004	Pink 

Resists clogging of cyanoacrylates. Use for microdot application of low viscosity fluids. Packaged 50 tips per box.

Precision Dispensing Tips

Chamfered Tips

Gauge	12.7 mm (0.50")	Color	
18	7018129	Green	
23	7018321	Orange	
25	7018352	Red	
33	7018482**	Clear	

Use for microdot application of low viscosity fluids. Packaged 50 tips per box.

**7018482 is 6.35 mm (0.25") long and packaged 25 tips per box..



PTFE-Lined Tips

ID	12.7 mm (0.50")	25.4 mm (1.0")	Color	
0.020"	7018256	7005003	Grey	
0.006"	7018388	7005004	Pink	

Resists clogging of cyanoacrylates. Use for microdot application of low viscosity fluids. Packaged 50 tips per box.

Polyethylene Nozzles

Size	Part #
6.35 x .318 cm (2.5 x .125")	7018555
6.35 x .157 cm (2.5 x .062")	7018557
10.6 x .157 cm (4.0 x .062")	7018559
10.6 x .08 cm (4.0 x .031")	7018561

Polyethylene nozzles thread into all cartridge sizes and 725 Series and 736HPA-NV valves. 1/4 NPT (6.35 mm) thread. Packaged 10 nozzles per bag.





Oval Tips

Gauge	12.7 mm (0.50")	Color	
15	7018078	Amber	

Flat ribbon deposits of thick pastes, sealants & epoxies. Outlet size is 1.98 x 0.41 mm (.078" x .016"). Packaged 50 tips per box.



Tip Shields

Size	Part #	Color	
3cc	7017715	Red	
5cc to 55cc	7017717	Black	

Reusable tip shields for light-sensitive and UV-cure adhesives. Fits over dispensing tip hub. Packaged 10 tip shields per box.



Metal Nozzles

Gauge	Part #	ID mm	ID inch
7	7017630	3.8	.150
8	7017633	3.4	.135
10	7017638	2.7	.106
12	7017643	2.2	.085
14	7017651	1.6	.063
16	7017660	1.2	.047

38.1 mm (1 1/2") long metal nozzles with 1/4 NPT to fit 725 Series and 736HPA-NV valves.

Precision Dispensing Tips

For Nordson EFD LLC sales and service in over 30 countries, contact Nordson EFD or go to www.nordsonefd.com

East Providence, RI USA
USA & Canada: 800.556.3484;
+1-401.431.7000
info@nordsonefd.com

Dunstable, Bedfordshire, UK
0800 585733; +44 (0) 1582 666334
Ireland 00800 8272 9444
europa@nordsonefd.com

China: +86 (21) 3866 9006
china@nordsonefd.com

Singapore: +65 6796 9522
sin-mal@nordsonefd.com

The Wave Design is a trademark of Nordson Corporation.
©2010 Nordson Corporation v021110

